

HHB SERIES

HOT WATER PRESSURE WASHERS

Tannehill

INDUSTRIES

Built to handle most rugged applications, the HHB Series also offers the portability required on jobsites.

Electric - Oil Heated - Belt Drive

- Belt drive triplex AR plunger pump
- 35-foot power cord
- Optional stack adapter allows 8-inch flue pipe to be installed to vent machine exhaust
- 13-inch solid tires with rear tire brake
- No.1 or No. 2 fuel oil, diesel or kerosene fired burner (Not approved for bio-fuel)
- Stainless-steel coil wrap
- Horizontal schedule 80 pipe coil
- Quick connect nozzles - 0°, 15°, 25° and 40° and low pressure nozzle (except on HHB-303-0E1A)



HHB-1502-0E1A

Additional Features:

Pump

- Thermal relief valve
- Easy pump oil drain

Motor

- Open drip-proof electric motor with thermal overload protection

Frame

- Wand holder
- Wrinkle-finish powder coated steel frame assembly

Components

- Racor fuel/water separator
- Pressure switch and high limit switch safety controls
- 35-foot power cord (GFCI with 20-amp plug on 1.5 to 6.0 HP, 1Ø models except on 208V, 1Ø models)
- Cam switch
- Motor pump
- Burner

- Adjustable thermostat
- Polyethylene float tank with inlet filter screen
- Adjustable high pressure detergent injection

Units Include:

- Insulated trigger gun with safety lock-off
- Adjustable pressure-insulated dual lance (except on HHB-303-0E1A)
- Single lance with dual insulated grips; steam nozzle (HHB-303-0E1A)
- 50-foot x $\frac{3}{8}$ -inch high pressure hose with quick connects (50-foot steam hose on HHB-303-0E1A)

Miscellaneous

- 300°F/149°C operating temperature (HHB-303-0E1A)
- Temperature rise 150°F/66°C above ambient, maximum outlet temperature is 200°F

HHB Series

Model Number	PSI	GPM	Horsepower/Motor	Plug Type	Burner Fuel Tank Cap.	Burner Fuel Cons.	BTU Per Hour	Dimensions (LxWxH)	Ship Wt.	Net Wt.
HHB-1002-0E1A	1000	2.0	1.5 HP, 115V, 1Ø, 16.2A	NEMA 5-20P	10.0 gallon	1.23 gph	172,200	57in.x30in.x41.5in.	606 lb.	486 lb.
HHB-1003-0E1A	1000	2.8	2.0 HP, 115V, 1Ø, 20.0A	NEMA 5-20P	10.0 gallon	1.84 gph	257,600	57in.x30in.x41.5in.	610 lb.	490 lb.
HHB-1502-0E1A	1500	1.8	2.0 HP, 115V, 1Ø, 19.9A	NEMA 5-20P	10.0 gallon	1.23 gph	172,200	57in.x30in.x41.5in.	610 lb.	490 lb.
HHB-2503-0E2A	2500	3.2	6.0 HP, 230V, 1Ø, 28.0A	NEMA 5-20P	10.0 gallon	1.84 gph	257,600	57in.x30in.x41.5in.	650 lb.	540 lb.
HHB-303-0E1A [^]	300	2.5	1.5 HP, 120V, 1Ø, 12.5A	NEMA 6-30P	10.0 gallon	2.76 gph	386,400	57in.x30in.x41.5in.	480 lb.	460 lb.

[^] Steam unit.



NEMA 5-30P,
30-amp plug



NEMA 5-20P,
20-amp plug



NEMA 5-15P,
15-amp plug

